Air King Ventilation Products®

SPECIFICATIONS
AK912
EXHAUST FANS

Bulb Heat Lamp
120 Volts, 2.0 amps, 60 hz.

- **Grill**
  White, polymeric grill (flame retardant ABS UL rated 94-5V) secured in place with torsion springs; easily removed if neccessary, dimensions - 10" x 10".
- **Heater Housing**
  23 gauge painted steel housing. Dimensions 8 1/4" x 8" x 5 7/8".
- **Lamping Information**
  1 - 250 watt maximum, type R40 bulb, medium base, 850 Btu.
- **Duct Collar**
  Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.
- **Unit Mounting**
  The housing will mount in ceilings with at least 6" of clearance and through drywall thickness up to 3/4", with a rough-in opening of 8 1/4" x 8". Rated for ceilings insulated to R-40. The housing will mount between 16" on center joists, using the 4 supplied housing mounting rails.
- **Single Pack Shipping Info**
  Box Dim: 14 1/2" x 11" x 8"
  UPC: 0-8316227021-4
  Shipping Weight: 5 lbs.



CUL - TYPE IC RATED

PROJECT		ARCHITECT	
LOCATION		ENGINEER	
CONTRACTOR		SUBMITTED BY	DATE

FAN NUMBER	MODEL NUMBER	CFM	IN W.G.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS

U.S.: 820 Lincoln Drive
West Chester, Pennsylvania 19380-4466
Tel: (877)-304-3785
Fax: (610) 696-8048

Canada: 110 Glidden Road
Brampton, Ontario L6T 2J3
Tel: (905) 456-2033
Fax: (905) 456-1015

Specifications subject to change without notice.

Updated 1-06

Downloaded from www.Manualslib.com manuals search engine